

# The Right Connections

## Sealed connection - Grabber®

PlymoVent was the pioneer of the inflatable tailpipe nozzle, which is today the industry standard. It's leakproof design guarantees no escape of exhaust gases from around your tailpipe.

### Grabber®

PlymoVent's Grabber connects the exhaust hose to the vehicle's exhaust pipe via an inflatable rubber bladder. The Grabber can be deflated manually by the operator, or automatically when the vehicle reaches the exit door. The unique rubber construction is perfect for applications that require a soft connection that will not damage the exhaust tailpipe.

- 100% capture of emissions
- High temperature construction, 315°C/600°F
- NOMEX® protective liner
- Will not damage vehicle
- Sizes for all applications



*The only 100% air tight solution!*



## TECHNICAL DATA

Grabber®, pneumatic exhaust nozzle with CO-outlet, incl 5 m/16 ft airline

Prod.no.	Dimension exhaust hose	Dimension Grabber	Weight	Max pressure	Temp resistance
GN-75-100	Ø 75 mm/3"	Ø 100 mm/4.0"	1.15 kg/2.55 lbs	1 bar/15 psi	+ 200°C/390°F
GN-100-100	Ø 100 mm/4"	Ø 100 mm/4.0"	1.10 kg/2.42 lbs	1 bar/15 psi	+ 200°C/390°F
GN-100-120	Ø 100 mm/4"	Ø 120 mm/4.8"	1.25 kg/2.75 lbs	1 bar/15 psi	+ 200°C/390°F
GN-100-160	Ø 100 mm/4"	Ø 160 mm/6.3"	2.05 kg/4.51 lbs	1 bar/15 psi	+ 200°C/390°F
GN-125-160	Ø 125 mm/5"	Ø 160 mm/6.3"	2.15 kg/4.73 lbs	1 bar/15 psi	+ 200°C/390°F
GN-125-200	Ø 125 mm/5"	Ø 200 mm/8.0"	2.35 kg/5.17 lbs	1 bar/15 psi	+ 200°C/390°F
GN-150-160	Ø 150 mm/6"	Ø 160 mm/6.3"	2.35 kg/5.17 lbs	1 bar/15 psi	+ 200°C/390°F
GN-150-200	Ø 150 mm/6"	Ø 200 mm/8.0"	2.40 kg/5.28 lbs	1 bar/15 psi	+ 200°C/390°F

*Pressure reducing valve must be ordered separately when required.*

Visit us on internet at: [www.PacAir.net](http://www.PacAir.net)